



**8202 Indy Lane
Indianapolis, IN 46214**

Product Data 2119

2119 is an excellent adhesive for edge glue applications, assembly, finger joint, and general-purpose woodworking and any other application where a high solids product is required on pre-finished parts including painted and stained. The adhesive has the ability to reduce the finish barrier and allow for a wood to wood mating. This product also works well with many exotic woods that contain high oils which make the glue operation difficult or not possible. The adhesive eliminates a wipe down step and allows immediate gluing procedures.

Physical Properties

Polyvinyl Acetate Water Based Adhesive

Appearance:	White,
Freeze/Thaw	Stable
Weight per Gallon	9.25 pounds
Solids	48 – 52 %
Viscosity	5500 – 6500 cps
Set Speed	Medium to Fast
Chalk Temperature	42 degrees F
Shelf Life	6 months @ 72 degrees F

The information on this Product/Technical Data sheet reflects the latest information and characteristics concerning this product. Seller makes no other warranty or representation of any kind, express or implied concerning this product including NO IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS OF THE GOODS FOR ANY OTHER PARTICULAR PURPOSE. NO WARRANTIES SHALL BE IMPLIED BY LAW AND NO AGENT OF SELLER IS AUTHORIZED TO ALTER THIS WARRANTY IN ANY WAY.

The exclusive remedy against seller shall be a claim for damages not to exceed the purchase price of the product, without regard to whether such a claim is based on breach of warranty or tort.