



**8202 Indy Lane
Indianapolis, IN 46214**

Product Data 5060

5060 is an excellent adhesive for edge glue applications, assembly, cold press lamination, fingerjoint, and general-purpose woodworking and any other application where a high solids product is required. Well mated, tight fitting joints with even pressure is essential to achieve adequate bonding. Moisture content should be in the range of 6 – 8 %. This product contains no fillers or extenders such as clays.

Physical Properties

Polyvinyl Acetate Water Based Adhesive

Appearance:	White, Brown, Yellow, or Red
Freeze/Thaw	Stable
Weight per Gallon	9.25 pounds
Solids	52%-56%
Viscosity	5500 – 6500 cps
Set Speed	Medium to Fast
Chalk Temperature	42 degrees F
Shelf Life	6 months @ 72 degrees F

The information reflects the latest information and characteristics concerning this product. Seller makes no other warranty or representation of any kind, express or implied concerning this product including NO IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS OF THE GOODS FOR ANY OTHER PARTICULAR PURPOSE. NO WARRANTIES SHALL BE IMPLIED BY LAW AND NO AGENT OF SELLER IS AUTHORIZED TO ALTER THIS WARRANTY IN ANY WAY.

The exclusive remedy against seller shall be a claim for damages not to exceed the purpose price of the product, without regard to whether such a claim is based on breach of warranty or tort.