



**INDUSTRIAL
ADHESIVES**
of Indiana

**8202 Indy Lane
Indianapolis, IN 46214**

Product Data 9002/9007

9002/9007 is a Water Based Contact Adhesive designed for quick tack, fast cure, and superior adhesion of vinyl's, foams, EXP's, PVC's, certain plastics, woods, non porous materials. This latex based one part adhesive must be applied to two sides of material, allowed to tack, dry is best and then joined. Pressure will increase the bond

Typical Properties

Total Solids	55-57%
Viscosity	500-1000 cps
PH	4.5-5.5
Odor	Slight
Color	White
Weight per gallon	8.8 pounds (U.S.)
Freeze/Thaw Stable	No
Open Time	10-15 minutes
Set Time	20 minutes. Overnight to fixture.
Water Resistance	Excellent
Wet Tack	Low
Coverage	780 sq. ft./gal. @ 3 grms/sq.ft.
Formaldehyde	None
VOC Content	Low

The information reflects the latest information and characteristics concerning this product. Seller makes no other warranty or representation of any kind, express or implied concerning this product including NO IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS OF THE GOODS FOR ANY OTHER PARTICULAR PURPOSE. NO WARRANTIES SHALL BE IMPLIED BY LAW AND NO AGENT OF SELLER IS AUTHORIZED TO ALTER THIS WARRANTY IN ANY WAY.

The exclusive remedy against seller shall be a claim for damages not to exceed the purpose price of the product, without regard to whether such a claim is based on breach of warranty or tort.