



**8202 Indy Lane
Indianapolis, IN 46214**

Product Data BG 1700

BG 1700 is a Water Based Poly Vinyl Acetate adhesive specifically formulated for the needs of the corrugated to corrugated manufacturer who manufacture a wax or NoMar coated box. This product performs well in many applications including hand folders, general automated folders, and high speed folders. With a high green tack, low run, and superior fiber tear on dry, BG 1700 also maintains open applicator nozzles during short normal down times. BG 1700 will suit the needs of any manufacturer. This product is pure in mixture and contains no clays, starches, or fillers.

Physical Properties

Vinyl Acetate Water Based Adhesive

Appearance:	White, Brown, Red, Blue
Freeze/Thaw	Stable
Tack/Hold Time	30-40 Seconds
Fiber Tear	5-8 Minutes
Weight per Gallon	9.25 pounds
Solids	52%-56%
Viscosity	1900-2300 cps
Set Speed	Fast
Chalk Temperature	42 degrees F
Shelf Life	6 months @ 72 degrees F

The information reflects the latest information and characteristics concerning this product. Seller makes no other warranty or representation of any kind, express or implied concerning this product including NO IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS OF THE GOODS FOR ANY OTHER PARTICULAR PURPOSE. NO WARRANTIES SHALL BE IMPLIED BY LAW AND NO AGENT OF SELLER IS AUTHORIZED TO ALTER THIS WARRANTY IN ANY WAY.

The exclusive remedy against seller shall be a claim for damages not to exceed the purpose price of the product, without regard to whether such a claim is based on breach of warranty or tort.