



INDUSTRIAL ADHESIVES *of Indiana*

8202 Indy Lane
Indianapolis, IN 46214

Product Data *HM 367*

HM 367 is a versatile pressure sensitive hot melt adhesive exhibiting superior high tack when liquid and dried. HM 367 is a hot melt adhesive that is formulated to adhere to a variety of difficult substrates at elevated temperatures. HM 367 carries a UL approval rating

Type	Formulated Hot Melt Adhesive,
Application	Aggressive Pressure Sensitive, Tack Free when cool
Viscosity	@500 F, 4200 cps + - 200
Open Time	Normal open time
Color	White
Shelf Life	One Year
Packaging	Meets composition requirements of indirect food additives

Production Use:

Adhesive will thin as temperature of equipment rises. Every application equipment is different and initial settings may have to be adjusted. If flow is too slow or heavy, product may be thinned by adjusting temperature by 10 degrees F until ideal flow rate is achieved. Heavy smoking of product is a sign of too high of temperature. To decrease flow rate, reverse temperatures by same amount.

“Meets composition requirements of indirect food additives”

The information reflects the latest information and characteristics concerning this product. Seller makes no other warranty or representation of any kind, express or implied concerning this product including NO IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS OF THE GOODS FOR ANY OTHER PARTICULAR PURPOSE. NO WARRANTIES SHALL BE IMPLIED BY LAW AND NO AGENT OF SELLER IS AUTHORIZED TO ALTER THIS WARRANTY IN ANY WAY.

The exclusive remedy against seller shall be a claim for damages not to exceed the purpose price of the product, without regard to whether such a claim is based on breach of warranty or tort.