



**INDUSTRIAL
ADHESIVES**
of Indiana

**8202 Indy Lane
Indianapolis, IN 46214**

Product Data *HM 717*

HM 717 is a versatile pressure sensitive hot melt adhesive exhibiting superior high tack when liquid and dried. It is sprayable, Can be used on Roll Coating operations. Adhesive is an excellent choice where superior strength after cure is required. This product is excellent for Polyethylene, Foam to wood, hard surfaces and any project where superior bond is required.

Type	Formulated Hot Melt Adhesive,
Application	Aggressive Pressure Sensitive, Tack Free when cool
Viscosity	@350 F, 1000 cps + - 200, not to exceed 400 F
Open Time	Normal open time
Color	May vary by type of packaging from gold to amber
Shelf Life	One Year
Packaging	3 pound block, 1 pound pouch (limited avail) Small bag package and brick type may be inserted In hot melt unit without removal of wrapping, Block type Packaging requires removal of wrapping.

Production Use:

Adhesive will thin as temperature of equipment rises. Every application equipment is different and initial settings may have to be adjusted. If flow is too slow or heavy, product may be thinned by adjusting temperature by 10 degrees F until ideal flow rate is achieved. Heavy smoking of product is a sign of too high of temperature. To decrease flow rate, reverse temperatures by same amount.

“Meets composition requirements of indirect food additives”

The information reflects the latest information and characteristics concerning this product. Seller makes no other warranty or representation of any kind, express or implied concerning this product including NO IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS OF THE GOODS FOR ANY OTHER PARTICULAR PURPOSE. NO WARRANTIES SHALL BE IMPLIED BY LAW AND NO AGENT OF SELLER IS AUTHORIZED TO ALTER THIS WARRANTY IN ANY WAY.

The exclusive remedy against seller shall be a claim for damages not to exceed the purpose price of the product, without regard to whether such a claim is based on breach of warranty or tort.