



8202 Indy Lane
Indianapolis, IN 46214

Technical Data Sheet CoreMaster XF (32)

Coremaster XF is a faster setting core and mold adhesive intended for use when silicate based products are too slow and hot melt glue is too fast or inconvenient to use. Core Master XF offers quick set time and superior strength after set. It performs well where many other core adhesives fail. Core Master XF- may be applied in a squeeze bottle or a grease gun applicator.

Specifications

Dry Time:	20 minutes - 1.5 Hours depending on ambient temperatures
Density:	11.57 #/gallon
Viscosity:	5500 cps
Specific Gravity:	1.52 gms/cc

Packaging

3 Lb, Quart, HDPE 28mm Bottle, 12/bottles/case

50 pound pails

540 pound, 55 gallon drums

Color: Rust Red, Neutral,

The information reflects the latest information and characteristics concerning this product under ASTM procedures. Seller makes no other warranty or representation of any kind, express or implied concerning this product including NO IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS OF THE GOODS FOR ANY OTHER PARTICULAR PURPOSE. NO WARRANTIES SHALL BE IMPLIED BY LAW AND NO AGENT OF SELLER IS AUTHORIZED TO ALTER THIS WARRANTY IN ANY WAY.

The exclusive remedy against seller shall be a claim for damages not to exceed the purpose price of the product, without regard to whether such a claim is based on breach of warranty or tort.